

Mounting angle MK

for the installation of the ventilated facade carcass



LANK/META

LANKSTYTI METALO PROFILIAI

Trakiškio g. 9, LT-35115 Panevėžys, Lithuania

Phone: +370 455 02310

Email: info@lankmeta.lt

Mounting angle type	Title of the mounting angle	Code for ordering	Metal type	Metal thickness, mm	h1, mm	h, mm	b, mm
MK Mounting angles without the strengthening edge							
	MK (70/50)x2,0 L=70	MK 50	S350GD+Z275	2	70	50	70
	MK (70/50)x2,5 L=70	MK 50	S350GD+Z275	2.5	70	50	70
	MK (70/60)x2,0 L=70	MK 60	S350GD+Z275	2	70	60	70
	MK (70/60)x2,5 L=70	MK 60	S350GD+Z275	2.5	70	60	70
	MK (70/70)x2,0 L=90	MK 70	S350GD+Z275	2	70	70	90
	MK (70/70)x2,5 L=90	MK 70	S350GD+Z275	2.5	70	70	90
	MK (70/80)x2,0 L=90	MK 80	S350GD+Z275	2	70	80	90
	MK (70/80)x2,5 L=90	MK 80	S350GD+Z275	2.5	70	80	90
	MK (70/90)x2,0 L=90	MK 90	S350GD+Z275	2	70	90	90
	MK (70/90)x2,5 L=90	MK 90	S350GD+Z275	2.5	70	90	90
We produce MK mounting angles of various specifications, attachment holes tailored to the client.							